



BGAN terminals

A quick reference guide



Inmarsat's Broadband Global Area Network service – BGAN – is accessible via a small, lightweight, satellite terminal, which is quick to set up and easy to use. And you can use the same device worldwide.

A range of terminals is available, including vehicular systems, providing performance options to suit different operational needs. The service is accessed via BGAN LaunchPad, a software interface, which is standard across all terminals.

					
Wideye™ Sabre™ I Voice and data, single-user device	EXPLORER® 110 Smallest, lightest device in the range	EXPLORER® 300 Highly compact, robust device	EXPLORER® 500 High bandwidth, highly portable device	HUGHES 9201 High performance, multi-user device	EXPLORER® 700 Multi-user device with extensive functionality

Terminals	Manufacturer:	Addvalue Communications www.wideye.com.sg	Thrane & Thrane www.thrane.com	Thrane & Thrane www.thrane.com	Thrane & Thrane www.thrane.com	Hughes Network Systems www.hughes.com	Thrane & Thrane www.thrane.com
	Size:	259 x 195mm (1.6kgs)	200 x 150mm (1kg)	217 x 168mm (1.4kgs)	218 x 217mm (1.4kgs)	345 x 275mm (2.8kgs)	297 x 399mm (3.2kgs)
	Standard IP:	Up to 240/384kbps (send/receive)	Up to 240/384kbps (send/receive)	Up to 240/384kbps (send/receive)	Up to 448/464kbps (send/receive)	Up to 492kbps (send & receive)	Up to 492kbps (send & receive)
	Streaming IP: (send & receive)	32, 64kbps	32, 64kbps	32, 64kbps	32, 64, 128kbps	32, 64, 128, 256kbps	32, 64, 128, 256kbps
	Voice:	Via RJ-11 or Bluetooth handset/headset	Via RJ-45 ISDN or Bluetooth handset	Via RJ-11 or Bluetooth handset/headset	Via RJ-11 or Bluetooth handset or 3.1kHz audio	Via RJ-45 ISDN handset, via ISDN TA with two RJ-11 ports for voice or 3.1 KHz for audio fax	Via RJ-11 (x2), Bluetooth handset or 3.1kHz audio
	ISDN:	N/A	N/A	N/A	64kbps via USB	64kbps via RJ-45	64kbps via RJ-45
	Other data interfaces:	Ethernet, Bluetooth	Ethernet (with adapter), USB, Bluetooth	Ethernet, Bluetooth	Ethernet, USB, Bluetooth	Ethernet, USB, WLAN 802.11b	Ethernet (x2), USB, Bluetooth, WLAN 802.11 a/b/g, Digital I/O
	Ingress protection:	IP 54	IP 44	IP 54	IP 54	IP 55	IP 52 (terminal), IP 66 (antenna)