EXPLORER 710



High-Speed, Portable BGAN Terminal

October 2020 Product Sheet



EXPLORER 710

High-Speed, Portable BGAN Terminal

Raising the BGAN bar

EXPLORER 710 is a portable satellite terminal set to usher in a new era in the world of BGAN by setting new standards for size, speed and features.

Smallest and Lightest

The smallest full Class 1 BGAN terminal positioned to support broadcasters by enhancing the quality of mobile outside broadcasting.



Specifications

inmarsa

Dimensions		
Total H / W / D:	332 / 279 / 54 mm	
	13.07 / 10.98 / 2.13 inches	
Total weight:	3.5 kg / 7.7 lbs (incl. battery)	
Antenna:	1.9 kg / 4.2 lbs	
Transceiver (incl. b	attery): 1.6 kg / 3.5 lbs	
Global Services		
Voice:	4 kbps AMBE+2	
Premium voice:	3.1 kHz audio, 64 kbps	
Standard IP:	Up to 492 kbps	
Streaming IP:	32, 64, 128 kbps	
	(256 kbps & BGAN X-Stream)	
HDR Streaming:	Min. 600 kbps	
	Min. 300 kbps (Half-channel	
HDR)		
ISDN:	UDI 64 kbps / RDI 56 kbps	
SMS:	Not supported	
Inmarsat frequencies	: 1518.0 - 1525.0 MHz (Rx) (EMEA)	
	1525.0 - 1559.0 MHz (Rx)	
	1626.5 - 1660.5 MHz (Tx)	
	1668.0 - 1675.0 MHz (Tx) (EMEA)	
EIRP:	20dBW ±1dB	
	PMOLED Display, 5 navigation keys, Audio and LCD pointing aids and LED indicator, Compass	
Languages:	UK, FR, DE, ES, RU and CN	
	Inmarsat Class 1 Type Approval at launch CE & FCC at launch. Other approvals TBC	

Fastest ever BGAN

The first and only BGAN terminal to support the full High Data Rate on-demand streaming service from Inmarsat. With speeds averaging 650 kbps, the EXPLORER 710 sets a new standard for mobile video newsgathering.

Double the speed with Plug & Play bonding; simply connect two EXPLORER 710 terminals with an ethernet cable and achieve streaming rates over 1 Mbps.

Interfaces

2 x LAN (RJ-45) interface	
Power over Ethernet:	PoE Cl. 2 on one RJ-45 interface
Max. cable length:	100m / 328ft (Cat5 UTP)
1 x USB host interface	
2.0 (host), Charging up t	to 2A
1 x ISDN interface	
Connector type:	RJ-45
Max. units per port:	8, max. total power supplied 1W
1 x Transceiver / Antenna i	interface
Connector type:	TNC-TNC
Max. cable loss:	1.4 / 20dB @ 1.5GHz
1 x BGAN SIM-Card slots	

Standard: IEEE 802.11 b/g

Environmental conditions

Temperature	
Operational (ambient):	-25°C to +55°C / -13°F to +131°F
Storage (excl. battery):	-40°C to +80°C / -40°F to +176°F
Battery storage temperatur	e
1 month:	-20°C to +60°C / -4°F to +140°F
3 months:	-20°C to +45°C / -4°F to +113°F
1 year:	-20°C to +20°C / -4°F to +68°F
Water and dust:	Transceiver: IP52 / Antenna: IP66
Relative humidity:	95% non-condensing
	at +40°C / +104°F

Power

Transmit time, max.:

Receive time, max .:

(25°C / 77°F)

Tower	
DC input range:	10-32VDC
Power consumption	
Intelligent Power Man	nagement 65W (max.)
AC/DC power supply	
Input:	100-240VAC, 47-63Hz, 65W
Output:	19VDC
Connector type:	2.5 / 5.5 mm power jack
Battery:	Lithium ion, rechargeable
Stand-by time:	36 hours

Subject to change without notice

2h30m @ 144 kbps

1h30m @ 650 kbps

3h30m @ 492 kbps



Smart and Easy

EXPLORER 710 introduces smart devices to the world of BGAN, enabling users to connect their own smart phone for terminal control, voice calls and connectivity. The EXPLORER Connect App with a SIP softphone is available on Android and IOS.

Other features include a USB host interface, hot-swappable batteries, a large easy-to-use LED display and multiple interfaces to support a wide range of applications.

Other features

Built-in SIP server Embedded Webserver Advanced Router with admin control Wireless Access Point Battery hot-swap and Built-in BGAN bonding Remote activation and remote management
EXPLORER Connect App for IOS and Android: Includes a SIP Softphone, Terminal Access to control your BGAN and Pointing Assistance.
EXPLORER Cellular Modem for USB: With the EXPLORER LTE Modem you can connect local cellular networks and use the EXPLORER 510 as wireless router for all your devices.

Package

EXPLORER 710 Transceiver & Antenna incl. rechargeable lithium ion battery, Antenna cable, 2m ISDN/LAN cable, 115/230VAC power supply, Quick start guide.

Accessories

000000000000000000000000000000000000000	
403720B-100	EXPLORER 710 Antenna
403686G	Lithium Ion Battery
403720B-010	Battery Hot Swap Cable
403682P	100-240V AC/DC Power Supply
403650A-009	Car Charger Cable
403670A-00500	IP Handset incl. Cradle
403650A-921	Pole Mount Kit
403720B-942	10m Antenna Cable
403720B-945	30m Antenna Cable
403720B-947	50m Antenna Cable
403720B-953	80m Antenna Cable
403756A-0500	EXPLORER Cellular USB Modem

Product number

403720B-00500

EXPLORER 710 Terminal

For further information please contact:

Cobham SATCOM Lundtoftegaardsvej 93 D DK-2800 Kgs. Lyngby Denmark Tel: +45 3955 8800